



To Order Parts:
 Phone 262.717.0477
 FAX: 262.717.0477
 EMAIL: Sales@USAutocorp.com

WebMax™ 1500 Series Spare Parts List (Models: 1514,1530,1546 & 1560)			System Compatibility	
			120 VAC	220VAC
LEVEL	PART NUMBER	DESCRIPTION		
Sensors & Cables				
1	USWD-S5	Sensor, WebMax NPN/PNP Output (Standard)	x	x
1	USWD-S5-1K	Sensor, WebMax 1KHZ Output (QuadTech Systems Only)	x	x
1	USWD-CAB-5M	Cable, WebMax Sensor 5 Meters	x	x
Master Control Unit & Power Supply				
3	USWD - PLC-1500	PLC, Complete (Includes pre-loaded software)	x	x
2	SDN-10-24-100P	Power Supply, Din Rail, Switcher, 240W	x	x
Display (HMI)				
3	HMI 520-TE	Display, WebMax HMI (Includes pre-loaded software)	x	x
Circuit Breakers & Relays				
3	1489-A1C200	Circuit Breaker, 20A,277V,1-Pole,C-Trip, SP Branch UL489 (Main Breaker)	x	
3	1492-SP1B010	1492 Supplementary Protectors, 1 pole, Magnetic Trip Range 3..5 x Rated Current (10% Arming Signal Breaker)	x	
3	1492-SP1B020	2A SP Supp UL 1077 B-Trip (PLC I/O)	x	x
3	1492-SP1C060	6A SP Supp UL 1077 C-Trip (Power Supply)	x	
3	1492-SP1B030	3A SP Supp UL 1077 B-Trip (Display)	x	x
3	1492-SP1C020	2A SP 1 pole, magnetic trip, range 5.10 x rated current (inductive loads) 2.0a (PLC Power)	x	
3	1489-A2C100	UL489/CSA 22.2 No 5.1 Circuit Breaker, 2 Pole, Trip Curve C, 10 Amp, 480Y/277 VAC (Main Breaker)		x
3	1492-SP2C030	1492 Supplementary Protectors, 2 pole, Magnetic Trip Range 10..20 x Rated Current (Highly Inductive Loads), 3.0 A (Power Supply)		x
3	1492-SP2C010	1492 Supplementary Protectors, 2 pole, Magnetic Trip Range 10..20 x Rated Current (Highly Inductive Loads), 1.0 A (PLC Power)		x
3	2961105	24 VDC Relay, 6 Amp (Systems with Web Severers Only)	x	x
3	782-2C-24D	24 VDC Relay, 2PDT (10% & E-Stop Circuits)	x	x
3	1492-SP1B030	3A SP Supp UL 1077 B-Trip (Sensor Output for 1514 Series)	x	x
3	1492-SP1B050	5A SP Supp UL 1077 B-Trip (Sensor Output for 1530 Series)	x	x

Parts Stocking Recommendations:

- LEVEL 1 - Highly Recommended
- LEVEL 2 - Recommended
- LEVEL 3 - Optional